

# HYDRAULICALLY DRIVEN ROTARY MOWER (60 inch Cut)

Description: The following description covers the requirements for a hydraulically driven zero turn radius, twin stick, commercial type mower capable of a 60 inch wide cut.

## Complies

### 1.0 General (Weight, Dimensions, Capacities)

1.01 Basic Overall Length: 75 – 88 inches

Y \_\_\_\_ N \_\_\_\_ Length: \_\_\_\_

1.02 Overall Width: 64 – 75 inches

Y \_\_\_\_ N \_\_\_\_ Width: \_\_\_\_

1.03 Dry Weight: 1,040 – 1,475 pounds

Weight: \_\_\_\_

1.04 Paint: Powder Coated or Epoxy List Color

Y \_\_\_\_ N \_\_\_\_ Color: \_\_\_\_

1.05 Hour Meter Oil Pressure, fuel Gauges

Y \_\_\_\_ N \_\_\_\_

1.06 Audio and Visual Alarms Provided

Y \_\_\_\_ N \_\_\_\_

1.07 Frame Construction: One Piece – Fully Welded

Y \_\_\_\_ N \_\_\_\_

1.08 Adjustable Twin Stick Type Steering System

Y \_\_\_\_ N \_\_\_\_

### 2.0 Engine – Powertrain

Make: \_\_\_\_

Model: \_\_\_\_

2.01 Gas, Air cooler Engine Electric

Y \_\_\_\_ N \_\_\_\_

2.02 Horsepower (gross): 26 – 35

Y \_\_\_\_ N \_\_\_\_ HP: \_\_\_\_

2.03 Fuel Capacity: 10 – 14 gallons

Y \_\_\_\_ N \_\_\_\_ Capacity: \_\_\_\_

2.04 Forward Speed: 0 – 13 mph

Y \_\_\_\_ N \_\_\_\_

2.05 Reverse Speed: 0 – 6 mph

Y \_\_\_\_ N \_\_\_\_

2.06 Transmission: Dual Hydrostatic Controls

Y \_\_\_\_ N \_\_\_\_

### 3.0 Wheels, Drive Tires

3.01 Dual or unitized Drive Motors

Y \_\_\_\_ N \_\_\_\_

3.02 Drive Tires: 25/26 x 12 x 9/12 (4 ply)

Tire Size: \_\_\_\_

3.03 Front Caster Tires: 13 x 6.5 (4 ply)

Tire Size: \_\_\_\_

3.04 Parking Brake: Hand Activated

Y \_\_\_\_ N \_\_\_\_

### 4.0 Mower Deck – Blades

4.01 Cutting Width: 60 inches

Y \_\_\_\_ N \_\_\_\_

4.02 Cutting Height: 1.0 – 5.0 inches

Height Range: \_\_\_\_

4.03 Foot Operated Height of Cut Adjustment

Y \_\_\_\_ N \_\_\_\_

4.04 Electromagnetic Clutch Engagement

Y \_\_\_\_ N \_\_\_\_

4.05 Deck Construction: Minimum ten (10) gauge steel

Y \_\_\_\_ N \_\_\_\_

4.06 Spindles bearing that can be lubricated

Y \_\_\_\_ N \_\_\_\_

4.07 Seat actuated blade kill switch

Y \_\_\_\_ N \_\_\_\_

### 5.0 Service Manuals, Warranty, Delivery Time

5.01 Provide complete literature and specifications on unit bid.

Y \_\_\_\_ N \_\_\_\_

5.02 State Warranty Period: (except belts, blades tires, and brakes) including parts and labor.

Y \_\_\_\_ N \_\_\_\_

Warranty Period \_\_\_\_

5.03 Specified Delivery Time (Not to exceed 60 days, upon receipt of order)

Y \_\_\_\_ N \_\_\_\_ Days: \_\_\_\_